

## 工业级光电转换器



型号	NCS1003	NCS1202	NCS1203
物理接口	最多支持2个百兆电口 最多支持1个百兆光口	最多支持1个千兆电口 最多支持1个千兆SFP插槽	最多支持2个千兆电口 最多支持1个千兆光口
MAC地址	1K	1K	4K
通信标准	IEEE 802.3: 10BaseT Ethernet IEEE 802.3u: 100BaseT(X) and 100BaseFX Fast Ethernet IEEE 802.3x: Flow Control	IEEE 802.3: 10BaseT Ethernet IEEE 802.3u: 100BaseT(X) and 100BaseFX Fast Ethernet IEEE 802.3ab: 1000BaseT(X) Ethernet IEEE 802.3z: 1000BaseX Ethernet IEEE 802.3x: Flow Control	
EMI	CISPR 22, FCC Part 15B Class A		
EMS	EN 61000-4-2 ( ESD ) Level 3 EN 61000-4-3 ( RS ) Level 3 EN 61000-4-4 ( EFT ) Level 3 EN 61000-4-5 ( Surge ) Level 3 EN 61000-4-6 ( CS ) Level 3 EN 61000-4-8 Shock: IEC 60068-2-27 Freefall: IEC 60068-2-32 Vibration: IEC 60068-2-6		
24V电压输入	4pin-可插拔端子 双电源 12~36VDC	4pin-可插拔端子 双电源 12~36VDC	4pin-可插拔端子 双电源 12~36VDC
220V电压输入	4pin-可插拔端子 单电源 85~264VAC/77~300VDC	4pin-可插拔端子 单电源 85~264VAC/77~300VDC	4pin-可插拔端子 单电源 85~264VAC/77~300VDC
电源功率	3W	3W	3W
工作温度	-40~+75° C		
储存温度	-40~+85° C		
相对湿度	5~95% ( 无凝霜 )		
外壳	IP40 金属外壳		
安装方式	默认导轨安装, 可选壁挂安装		
保修期	5 年		